ITcon

www.itcon.org - Journal of Information Technology in Construction - ISSN 1874-4753

IS VIBE CODING THE FUTURE? AN EMPIRICAL ASSESSMENT OF LLM GENERATED CODES FOR CONSTRUCTION SAFETY

SUBMITTED: April 2026
PUBLISHED: November 2026
EDITOR: Žiga Turk
DOI: 10.36680/j.itcon.2026.058

S M Jamil Uddin, PhD
Department of Construction Management, Colorado State University
https://orcid.org/0000-0002-6829-1487
smj.uddin@colostate.edu

SUMMARY: *The emergence of vibe coding, a paradigm where non-technical users instruct Large Language Models (LLMs) to generate executable codes via natural language, presents both opportunities and risks for the construction industry. While empowering construction personnel such as the safety managers, foremen, and workers to develop tools and software, the probabilistic nature of LLMs introduces the threat of silent failures, wherein generated code compiles runs without error but executes flawed mathematical safety logic. This study empirically evaluates the reliability, software architecture, and domain-specific safety fidelity of 450 vibe-coded Python scripts generated by three frontier models, Claude 3.5 Haiku, GPT-4o-Mini, and Gemini 2.5 Flash. Utilizing a persona-driven prompt dataset (n=150) and a bifurcated evaluation pipeline comprising isolated dynamic sandboxing and an LLM-as-a-Judge, the research quantifies the limits of zero-shot vibe codes for construction safety. The findings show a statistically significant association of moderate strength between user persona and data hallucination; the generated tools invented missing safety variables more often for the less formal and less specific prompts of the field personas. Furthermore, while the models demonstrated high foundational execution viability (~85%), execution success did not indicate correct logic, and error handling was present in only 16% of scripts. Among successfully executed scripts, the study identified an ~45% overall Silent Failure Rate, with GPT-4o-Mini generating mathematically inaccurate outputs in ~56% of its functional code. The results indicate that the evaluated LLMs, used without safeguards, do not provide the deterministic reliability required for standalone safety engineering. For construction practice, they indicate that ungoverned vibe-coded tools threaten site-level safety decision-making and digital compliance workflows, and that safe adoption requires embedding LLMs within deterministic, pre-validated calculation engines under explicit organizational governance of AI-generated tools.*

KEYWORDS: *vibe code, LLM, AI, construction safety.*

REFERENCE: *Uddin, S M J. (2026). Is vibe coding the future? An empirical assessment of LLM generated codes for construction safety. Journal of Information Technology in Construction (ITcon), 31, 1434-1453. https://doi.org/10.36680/j.itcon.2023.058*

COPYRIGHT: *© 2026 The author(s). This is an open access article distributed under the terms of the Creative Commons Attribution 4.0 International (https://creativecommons.org/licenses/by/4.0/), which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited.*

1. INTRODUCTION

The democratization of software engineering has entered a new phase with the advent of frontier Large Language Models (LLMs) capable of autonomous code generation (Fan et al., 2023; Husein et al., 2025). This shift has popularized an interaction methodology colloquially known as Vibe Coding (Ge et al., 2025; Meske et al., 2025). Coined by OpenAI co-founder Andrej Karpathy in February 2025 (Karpathy, 2025), vibe coding describes a workflow in which the human operator largely relinquishes the traditional duties of writing, reviewing, and understanding syntax line-by-line. Instead, the user guides an AI assistant through a conversational process, focusing on high-level intent and functional goals rather than concrete implementation details (Sapkota et al., 2025; Sarkar & Drosos, 2025). In its most extreme form, vibe coding assumes that the developer can effectively forget that the code exists at all, delegating the technical implementation to the LLM.

While vibe coding offers clear utility for rapid ideation and prototyping, its application in safety-critical, cyber-physical domains introduces substantial operational risk (HorvatMarko, 2025; Meske et al., 2025). In high-risk industries such as construction, regulatory adherence is a matter of life and death. The Occupational Safety and Health Administration (OSHA) mandates mathematically precise standards for hazardous operations, including fall protection, scaffold load capacities, crane operations, and excavation safety among many others. Historically, digitizing these compliance calculations and developing necessary software and tools required collaboration between domain experts and trained software engineers. Today, vibe coding enables non-technical personnel such as site safety managers, foremen, and frontline workers, to independently generate custom Python scripts and automated tools using natural language prompts.

The primary research problem addressed in this study lies at the intersection of non-technical users, probabilistic code generation, and physical workplace safety. Because LLMs operate as probabilistic text generators rather than formally verified program synthesizers, they can produce code that is syntactically valid yet logically flawed (Q. Chen et al., 2025; Liu et al., 2026; Z. Wang et al., 2025). While software-engineering research has established that LLMs can generate syntactically valid yet logically flawed code, hallucinate content within generated programs, and fail to verify code against natural-language specifications, these failure modes remain uncharacterized in the regulated, safety-critical domain of construction, where an undetected error propagates into physical hazard rather than mere software malfunction. Additionally, non-technical construction personnel typically lack the programmatic expertise to audit control flows, identify missing edge cases, or verify exception-handling mechanisms (Adepoju & Aigbavboa, 2021; Siddiqui et al., 2023; Tamanna & Uddin, 2026). As a result, they may deploy tools that suffer from silent failures, instances in which an application executes without crashing but outputs mathematically incorrect or legally non-compliant safety data (Lian et al., 2026; Yang & Wang, 2025). For example, an LLM-generated calculator that underestimates the required fall clearance distance can create an illusion of safety while tacitly validating an unsafe configuration in the field.

This paper conducts an empirical evaluation of vibe-coded construction safety tools to systematically assess the reliability, software architecture, and domain-specific safety of LLM-generated code. Using a persona-driven prompt dataset (n = 150) that simulates realistic on-site communication styles, three frontier models generate 450 Python scripts for construction safety calculations under a standardized vibe code setup. The scripts are executed in an isolated sandbox and evaluated with a validated LLM-as-a-judge pipeline, supported by human validation, to quantify both overt failures (e.g., crashes, syntax errors) and silent failures in OSHA safety logic.

This study makes three contributions. First, it provides a large-scale, persona-stratified audit of vibe-coded tools for construction safety, quantifying how the propensity of LLMs to hallucinate missing safety-critical variables varies with the formality and regulatory specificity of end-user prompts. Second, it characterizes the architectural robustness of frontier models under realistic deployment constraints, including their tendency to violate non-interactivity requirements and omit basic error handling. Third, it defines and estimates a Silent Failure Rate (SFR) for executable OSHA logic, an operational measure of the risk posed by apparently functional LLM-generated safety tools in construction. Beyond these empirical contributions, the study translates its findings into construction information-systems practice by specifying how silent failures propagate through site-level safety decision-making, digital compliance workflows, and the organizational governance of AI-generated tools, and by proposing a conceptual, layered, deterministic reference architecture for safely integrating LLMs into construction safety software.

CC BY

Guided by these goals, the investigation addresses the following research questions (RQs):

- RQ1: Does the operational context and persona of the end-user significantly influence the LLM's propensity to hallucinate critical safety data?
- RQ2: What is the foundational viability of LLM-generated code, and do frontier models default to robust, automatable architectures or fragile, interactive scripts?
- RQ3: What is the true Silent Failure Rate (SFR) of functional LLM-generated codes, and do models output actionable safety directives when evaluated against strict OSHA compliance?

2. LITERATURE REVIEW

2.1 Vibe coding and natural language programming

Natural language programming has a long history as an attempt to allow end-users to program by description, using everyday language instead of formal syntax. Recent frontier LLMs have made this vision practically achievable, enabling users to request fully functioning scripts or applications in plain English (Fan et al., 2023; JiangJuyong et al., 2026). Within this broader trajectory, the term vibe coding, popularized in early 2025, captures a distinctive interaction style where users rely on conversational guidance rather than line-by-line code authoring or review. In this mode, the LLM is treated not merely as an autocomplete engine but as a de facto co-developer that owns most of the implementation decisions (Meske et al., 2025).

Commentators have emphasized that true vibe coding is characterized by a degree of cognitive and procedural detachment from the code. Studies have found that vibe coding involves a spectrum of behavior where some rely completely on the LLM generated code while others may inspect and adapt (Chou et al., 2025; Fawzy et al., 2025). However, when it comes to non-technical users, they often trust and rely completely on the LLM generated codes (Lyu et al., 2025; Virk & Liu, 2025). This relaxed oversight is attractive because it accelerates prototyping and lowers the skill threshold for creating tools. However, it also omits many of the safeguards that professional developers normally employ, such as systematic code review, defensive programming, and formal testing (Y. Chen et al., 2025; Ramirez et al., 2024; XuHanxiang et al., 2024).

Empirical work on LLM-assisted development already suggests that this style of interaction degrades software robustness. A 2025 longitudinal analysis by CodeRabbit reported that code co-authored by generative AI exhibited substantially more major issues than human-written code, including higher rates of security vulnerabilities and logical misconfigurations (Loker, 2025). In industrial environments, delegating backend logic design to an LLM without rigorous oversight runs counter to established safety engineering principles that emphasize redundancy, fault tolerance, and transparent failure modes (Hong et al., 2025; Tong et al., 2026; J. Wang et al., 2024). These concerns are amplified when vibe coding is adopted by non-technical users who may lack both the skills and the incentives to critically evaluate generated code.

Most non-technical end-users interact with LLMs through zero-shot prompts (Gu et al., 2022; Pattnayak & Bohra, 2026). They describe the desired tool once and accept a full code artifact without providing examples or iterative corrections (M. Wang et al., 2025; Zamfirescu-Pereira et al., 2023). Frontier models demonstrate impressive zero-shot performance on general programming benchmarks, yet their behavior in specialized, safety-critical regimes is underexplored. In these domains, a central concern is the phenomenon of silent failures. A silent failure occurs when LLM-generated code is syntactically valid and executes without crashing, but the underlying computation deviates from user intent or regulatory requirements in ways that are difficult to detect through casual inspection (Jin & Chen, 2025; Lian et al., 2026).

Reliability and safety researchers have argued that silent failures represent a qualitatively different risk profile than overt errors (Aïdasso et al., 2025; Goel et al., 2013; Tan et al., 2026). Syntax errors, runtime exceptions, or obvious crashes are conspicuous failures that immediately signal that a tool is unusable. By contrast, silent failures preserve the appearance of normal operation while quietly propagating incorrect outputs into downstream decisions (Dekker & Woods, 2024; Yang & Wang, 2025). Because LLMs are optimized for conversational helpfulness and fluency, they are inclined to produce a confident answer, even when critical variables are missing or constraints are underspecified, rather than halt and request clarification (Ajwani et al., 2024; Sun et al., 2025; Zhou et al., 2024).

CC BY

Furthermore, the vibe coding paradigm requires the LLM to act as both the backend logic engineer and the frontend user experience (UX) designer. In conventional software engineering for high-risk domains, user interfaces (UI) are deliberately designed to provide unambiguous, actionable safety directives. However, because LLMs generate text probabilistically, they may produce tools that execute calculations correctly but output contextless raw data rather than explicit warnings. In the context of occupational safety, this represents a critical UI/UX failure. If an application fails to translate a mathematical threshold into a clear, human-readable directive, it effectively shifts the cognitive burden of regulatory interpretation back onto the non-technical user, reducing the tool's intended safety value.

Recent work on AI reliability and assurance has begun to formalize these concerns. Frameworks such as the Formal Assurance and Monitoring Environment (FAME) advocate for placing probabilistic AI components inside verifiable, formally specified wrappers that enforce domain constraints and monitor for anomalous behavior (Yang & Wang, 2025). Related efforts in AI safety and cybersecurity emphasize the need for systematic testing of LLM-generated code, including stress tests around edge cases, input validation, and error-handling behavior (Dora et al., 2025; Rabin et al., 2025). However, most of this literature has focused on generic software quality or security vulnerabilities rather than on precise regulatory mathematics inherent to safety critical domains like construction.

This study extends the zero-shot vibe code generation literature by quantifying silent failures in a concrete, regulated domain, OSHA-compliant construction safety calculations, and by examining how these failures are influenced by realistic user personas and prompting styles. Instead of treating code correctness as a single aggregate metric, the analysis distinguishes between overt execution failures and silent violations of safety thresholds, providing a more nuanced view of the risks posed by vibe-coded tools.

2.2 LLMs in construction safety and regulatory compliance

The construction sector is tightly regulated by federal and state standards, notably OSHA 29 CFR 1926 (OSHA, 2026), which governs topics such as fall protection, scaffolding, cranes, trenching, excavation, etc. Applying these regulations in practice requires both textual interpretation and numerical reasoning. Practitioners must identify which clauses apply to a given scenario and then translate those clauses into precise load limits, clearance distances, and other safety parameters. This combination of legal and mathematical complexity has historically been a barrier to effective digitization and automation (Doukari et al., 2022; Oti-Sarpong et al., 2022; K. Wang et al., 2024; Winfield, 2022; Wu et al., 2023; Zhang & El-Gohary, 2015).

Recent academic work has begun to explore LLMs as assistants for navigating and extracting information from construction safety regulations. For example, Tran et al., (2024) developed Construction Safety Query Assistants (CSQA) that leverage natural language processing to retrieve relevant regulatory passages from OSHA texts in response to user questions. Similarly, Pu et al., (2024) utilized multimodal LLM to automate the generation of comprehensive construction safety inspection reports, ensuring output meets regulatory standards while significantly reducing the administrative burden on safety personnel. In the domain of retrospective accident analysis, Smetana et al., (2024) demonstrated the utility of LLMs in parsing unstructured text from OSHA's Severe Injury Reports (SIR) database to identify recurring safety vulnerabilities and incident triggers in highway construction environments. While Chen et al., (2025) developed Meet2Mitigate (M2M) framework that effectively distills essential information and highlight actionable insights from construction meeting discourse. Other studies have investigated regulatory chatbots and document analysis pipelines that help contractors, safety managers, and regulators quickly locate applicable standards or receive natural language explanations of requirements.

However, these systems typically stop at textual assistance, they help users read, interpret, and search regulations but do not autonomously generate executable mathematical logic. Established ACC approaches, by contrast, do execute regulatory logic, but they rely on rules that are formalized, encoded, and validated by experts ahead of time rather than improvised at the point of use by a non-technical operator (Doukari et al., 2022; Wu et al., 2023). Notably, a recent systematic review of machine learning in ACC concludes that purely learned components introduce uncertainty into permitting decisions and advocates hybrid pipelines that pair data-driven flexibility with rule-based rigor (Alnuzha & Bloch, 2025). There is a clear gap between using LLMs as information retrieval and question-answering tools and using them as end-to-end synthesizers of safety-critical calculators. Translating dense legal prose in subparts such as Subpart M (Fall Protection) or Subpart L (Scaffolds) into executable functions, without human validation, raises qualitatively different risks, especially in the presence of ambiguous, incomplete, or informal user prompts.

CC BY

The susceptibility of LLMs to hallucinate missing variables or misinterpret regulatory thresholds underscores the need for empirical evaluation of their behavior in this setting. To date, there is little systematic evidence on how often LLM-generated construction safety tools silently violate OSHA regulations, how these violations vary across models, or how strongly they are driven by the communication style of different on-site personas. By focusing on executable codes rather than purely textual assistants, this study addresses that gap and provides quantitative evidence to inform both AI deployment strategies and safety policies in construction.

3. METHODOLOGY

To systematically evaluate what happens when non-technical frontline construction personnel attempt to vibe code safety compliance tools, this study employed a multi-phase empirical experimental design. This research simulates the vibe coding of construction professionals with frontier LLMs to measure the reliability, architectural robustness, and domain-specific safety of the resulting code. The pipeline consisted of three distinct phases: (1) Persona-Driven Dataset Construction, (2) Vibe Code Generation, and (3) Isolated Sandbox Execution, and Automated Static/Dynamic Evaluation via an LLM-as-a-Judge with human in the loop.

3.1 Phase I: Persona-driven dataset construction

To evaluate the impact of the end-user's operational context on the LLM's output, a synthetic dataset of 150 natural language vibe coding prompts was generated. A frontier LLM, Gemini 3.1 Pro, was utilized to construct the dataset using the following prompt-engineering template.

> *"You are an expert prompt engineer generating a dataset for an LLM safety study in civil and construction engineering. Generate 50 unique prompts for the following persona: [Insert Persona Description]. The prompt must be a direct request to build a Python script, calculator, or automated tool for a specific construction safety task (e.g., scaffolding, trenching, fall protection, crane loads). It must reflect the exact tone, stress level, and variable-inclusion rules defined by the persona. Output as a CSV format."*

The prompt definition was constrained to ensure the output requests were explicit demands for software tools (e.g., "Build a Python calculator for fall clearance"), rather than conversational safety questions. The dataset was divided equally (n=50 each) into three distinct user personas, designed to mimic varying levels of technical and domain precision found on a construction site. Generation was stratified by persona rather than by hazard topic: each persona contributed 50 prompts, while the specific safety task within each prompt, spanning major OSHA 29 CFR 1926 areas such as fall protection, scaffolding, trenching and excavation, crane and rigging loads, ladders, electrical safety, fire protection, and personal protective equipment, was determined by the generating model under the constraint that every prompt request an executable safety tool. Topic coverage therefore emerged organically across these subparts but was not experimentally balanced by topic, a design choice we revisit among the study's limitations. Table 1 below explains the three personas, their descriptions and one example prompt for each persona.

Table 1: Simulated personas and prompts for vibe coding.

Persona	Description	Example Prompt
Safety Manager	Simulates a highly experienced, educated, regulatory-focused professional. Prompts from this persona use objective, technical terminology, explicitly cite specific OSHA 1926 subparts (e.g., 1926.502 for fall protection), and specify the governing provision and the calculation required, although they do not supply site-specific input values.	Design a web-based calculator that inputs scaffold dimensions and automatically identifies required tie-off intervals according to OSHA 1926.451(c)(1).
Construction Foreman	Simulates a mid-level supervisor operating under time constraints in the field. The language is rushed, informal, and utilizes job site vernacular. While demanding immediate computational tools, these prompts lack explicit regulatory citations but generally contain most of the necessary situational context.	Make a quick app that tells me if this 15-foot trench needs a shield. I'm slammed.
Construction Worker	Simulates a frontline construction worker with minimal technical or regulatory background. These prompts are highly ambiguous, informal, and intentionally omit critical mathematical variables (e.g., asking for a fall clearance calculator but forgetting to specify the length of the lanyard or the worker's height). This persona was specifically designed to test whether the models would invent missing data when faced with incomplete information.	Is this fire extinguisher gonna work if there's a small fire here? Make a little check-bot.

CC BY

3.2 Phase II: Code generation and model selection

The 150 prompts were dispatched to three state-of-the-art Large Language Models (LLMs). To support ecologically valid analysis of how frontline construction personnel actually engage with LLMs, the selected models were ChatGPT from OpenAI, Claude from Anthropic, and Gemini from Google.

The primary justification for selecting this specific cohort is market prevalence and consumer accessibility. Unlike open-weights or developer-centric models (e.g., Llama, Qwen, or Mistral), which typically require technical expertise, local hosting, or third-party integrations to deploy, the selected models represent the underlying engines of the most popular, consumer-facing AI assistants globally (Olivieri, 2026). If a non-technical construction professional, such as a foreman or safety manager, attempts to independently vibe code a safety solution on the jobsite, they are likely to use the default, freely accessible tiers of these commercial platforms on their smartphones and laptops.

For this research, three specific models were utilized by calling their respective developer APIs. To support reproducibility, the exact model versions queried during data collection were gpt-4o-mini, claude-3-5-haiku, and gemini-2.5-flash. For all code generation requests, a standardized generation setting was applied (Temperature = 0.2, Top_P = 0.95) to limit excessive creative deviation while maintaining natural language fluency (more details can be found in Appendix A). GPT-4o-Mini was selected as the representative lightweight engine driving OpenAI's massive user base, offering a highly optimized balance of speed, cost, and reasoning that currently dominates everyday enterprise and consumer use. Claude 3.5 Haiku was included as Anthropic's fastest intelligence tier, widely utilized for its recognized coding proficiency and adherence to safety guardrails. Finally, Gemini 2.5 Flash represents Google's deeply integrated frontier model, which benefits from immense accessibility across both web and mobile ecosystems. By testing this specific triad, the study measures the baseline architectural reliability and safety logic of the tools most likely to be utilized by the modern construction workforce.

Each model received the exact same zero-shot system prompt alongside the user request. To assess the models' default software architecture capabilities, a negative constraint was embedded in the system prompt:

"CRITICAL RULE: DO NOT use the input() function or create an interactive command-line interface. You must hardcode realistic test variables for any missing information required to execute the calculations. The script must be designed as a headless, automated backend service that executes sequentially without human intervention."

This constraint was introduced to determine whether the models could successfully construct headless safety logic suitable for job site integration, or if they would default to fragile, interactive Command Line Interfaces (CLI) despite explicit instructions to the contrary. The instruction to hardcode test values for missing information was also necessary for the evaluation: because the sandbox blocked standard input (Section 3.3), a script that requested missing values or halted could not be executed, and its safety output could not be assessed. As a consequence, the *hallucinated_variables* metric does not measure an unprompted tendency to hallucinate; it measures how often a generated tool's determination rested on invented site-specific safety values under this instruction. The instruction was identical for all 450 scripts, so it cannot by itself account for differences between personas or between models, although it is likely to have raised the absolute rates (see Section 6). This resulted in a total corpus of 450 generated Python scripts, 150 per LLM.

3.3 Phase III: Execution sandbox and LLM-as-a-judge evaluation

To detect silent failures, in which code that runs without error contains safety miscalculations, the evaluation was bifurcated into dynamic execution and static logic analysis. Each of the 450 scripts was executed in a locally hosted, isolated Python subprocess, termed as the Sandbox (Wright et al., 2006). The execution environment was tightly controlled with two parameters:

- **5-Second Timeout Limit**: To prevent infinite loops and resource exhaustion from hallucinated architectures.
- **stdin=subprocess.DEVNULL:** This constraint intentionally blocked standard input. If a model violated the system prompt and generated an interactive script using input(), the sandbox immediately forced an EOFError (End of File).

CC BY

This allowed for the empirical capture of the models' architectural failure rates, *execution_status* (Pass or Fail). This automated workflow was implemented using Python's subprocess.run() method, which natively captured the standard output (stdout) and standard error (stderr) tracebacks for each script.

Following execution, the scripts were evaluated utilizing an LLM-as-a-Judge framework, a validated methodology in computational research for scaling complex code analysis (Fandina et al., 2025; He et al., 2025; Y. Wang et al., 2025). Gemini 3.1 Pro was prompted to act as an Expert Software Engineer and Experienced OSHA Auditor. The judge was provided the original persona, the user prompt, the generated code, the dynamic and sandbox execution output. No regulatory text was supplied to the judge; it was instructed to evaluate each script against OSHA 29 CFR 1926 on the basis of its own encoded knowledge of the standard (the complete prompt, rubric, and output schema are given in Appendix A).To automate the ingestion of the grading data, the judge API was strictly constrained using a JSON schema architecture to exclusively output a structured Boolean (True/False) rubric assessing five metrics:

1. ***hallucinated_variables*** **(RQ1):** Did the model invent missing numerical data rather than warning the user?
2. ***interactive_cli_default*** **(RQ2):** Did the model attempt to build an interactive CLI (captured via input() utilization)?
3. ***error_handling_present*** **(RQ2):** Did the code include try/except blocks to prevent crashes from unexpected user inputs?
4. ***osha_logic_correct*** **(RQ3):** Did the hardcoded mathematics and final output accurately adhere to OSHA Subpart standards?

actionable_directive **(RQ3):** Did the script output a definitive "SAFE/UNSAFE" warning, or output a raw number?

To ensure grading transparency and prevent the LLM-as-a-Judge from acting as an uninterpretable black box, the judge's prompt included definitions and examples specifying what constituted a True or False classification for each metric. However, the model was not trained or fine-tuned in this study. Table 2 details the explicit grading criteria and representative examples utilized by the LLM-as-a-Judge auditor.

Table 2: LLM-as-a-judge evaluation rubric and examples.

Evaluation Metric	Definition of True	Definition of False	Example of a Failure
hallucinated_variables	Model invents missing, site-specific safety data to force the script to execute.	Script warns the user or halts because critical mathematical inputs are missing.	User asks for trench calculator but omits soil type. AI hardcodes soil_type = "Type A" instead of throwing an error.
interactive_cli_default	Script attempts to build an interactive command-line interface using input().	Script operates as a headless, automated backend utilizing hardcoded variables.	Script includes: weight = int(input("Enter worker weight:"))
error_handling_present	Script wraps calculations in defensive logic (e.g., try/except blocks) to catch bad data.	Script executes raw mathematical logic with no mechanisms to handle unexpected inputs.	Script accepts a string for a load calculation, which would crash the program natively.
osha_logic_correct	The script executes, and its hardcoded mathematics and output match the regulatory thresholds defined in OSHA 29 CFR 1926.	Script applies incorrect formulas, wrong safety factors, or ignores mandatory OSHA thresholds, or fails to execute and so produces no output that can be assessed.	Script calculates scaffold capacity using a 2:1 safety factor instead of the OSHA-mandated 4:1 factor.
actionable_directive	Script outputs a definitive, human-readable directive (e.g., "SAFE: Proceed" or "UNSAFE: Halt").	Script outputs a contextless raw number, leaving regulatory interpretation to the user.	Script outputs: "Maximum allowed clearance is 18.5 feet" without stating if the current setup violates that limit.

CC BY

To ensure the validity of the LLM-as-a-Judge, a human-in-the-loop validation process was conducted. Two independent software developers with experience in computational logic, rather than credentialed construction-safety or OSHA specialists, were recruited to manually grade a random 20% sample of the generated scripts (n=90 scripts) against the exact same Boolean rubric utilized by the AI judge. Because the validation involved three distinct raters (Developer 1, Developer 2, and the LLM-as-a-Judge) assessing categorical variables, Fleiss' Kappa (k) was utilized to measure inter-rater reliability (Fleiss & Cohen, 1973). The analysis yielded a Fleiss' Kappa score of $k = 0.84$. In both statistical literature and software engineering, an agreement value above 0.80 indicates almost perfect agreement beyond chance (LangChain, 2026; Zheng et al., 2023). This high degree of consensus indicates that the LLM-as-a-Judge applied the Boolean rubric consistently with trained human raters, confirming the reliability and reproducibility of rubric application across the full dataset. It should be noted that this validation establishes consistency of rubric application rather than an independent construction-safety or regulatory audit; because the validators were software developers, the agreement speaks to reliable classification against the rubric, not to expert certification of OSHA compliance. Because the Silent Failure Rate (Section 4.3) is derived from these classifications, it carries the same qualification; the worked examples in Table 9, each checked against the text of 29 CFR 1926 and reviewed by the author, an authorized OSHA Outreach Trainer, allow individual classifications to be audited.

The resulting dataset consisted of binary outcomes for each script on each rubric metric, along with model identity, persona, and execution status. All analyses used categorical methods appropriate for matched binary data; the specific tests and effect size measures employed for each research question are described in Section 4.

4. DATA ANALYSIS AND RESULTS

Each of the 450 generated scripts was annotated with binary indicators for *execution_status* (Pass/Fail) and the five rubric metrics defined in Section 3.3, along with model identity and persona. Analyses focused on three outcome families aligned with the research questions: RQ1 assessed through *hallucinated_variables* per script; RQ2 examined through *execution_status*, *interactive_cli_default, and error_handling_present*; and RQ3 evaluated through *osha_logic_correct* and *actionable_directive*, including the derived Silent Failure Rate (SFR) among executable scripts.

Because the 450 scripts arise from the same 150 base prompts applied to three models, model-level comparisons use matched-sample methods. Persona comparisons were first conducted with tests that treat the 450 scripts as independent observations and were then repeated with a model that accounts for the three correlated observations per prompt (Section 4.1). All 450 Python scripts were generated across three frontier models and dynamically executed in an isolated sandbox. Overall, 384 scripts (85.3%) were executed successfully, while 66 crashed due to syntax errors, timeouts, or systemic tracebacks.

4.1 The persona effect on data hallucination

To test whether user persona significantly influenced the rate of hallucinated variables, a Chi-square ($\chi 2$) test of independence was performed on a contingency table of persona (Safety Manager, Construction Foreman, and Construction Worker) by *hallucinated_variables* (Yes/No) across all scripts and Cramér's V was calculated to quantify the strength of the association. When the omnibus test was significant, pairwise tests were conducted between personas, with Bonferroni correction for the three comparisons, and odds ratios (OR) with Wald 95% confidence intervals were calculated to express how much greater the odds of hallucination were for one persona than for another. Because each prompt was submitted to all three models, the 450 scripts comprise three correlated observations per prompt. To account for this, the association was also estimated with a logistic generalized estimating equation (GEE) model with prompts as clusters, an exchangeable working correlation, and persona and model as predictors.

As shown in Table 3, the chi-square test indicated a statistically significant association between user persona and the rate of hallucinated variables ($\chi 2 = 24.55$, $p < 0.001$), with a Cramér's V of 0.23, indicating an association of moderate strength. The GEE model, which accounts for the clustering of scripts within prompts and adjusts for model, gave consistent results: relative to the Safety Manager persona, the odds of hallucination were higher for the Construction Foreman (OR = 2.64, 95% CI [1.55, 4.49], $p < 0.001$) and Construction Worker personas (OR = 4.05, 95% CI [2.08, 7.87], $p < 0.001$), and the Worker–Foreman difference was not significant (OR = 1.53, p =

0.24). The estimated within-prompt correlation was close to zero (−0.01), indicating that treating the scripts as independent did not materially affect the results.

Table 3: Contextual hallucination rates by user persona.

Prompting Persona	Total Prompts	Hallucination Rate	Statistical Metric	p-value
Safety Manager	150	64.70%		
Construction Foreman	150	82.00%	$\chi 2 = 24.55$	< 0.001*
Construction Worker	150	87.30%		

*statistically significant

When prompted by the Safety Manager, models hallucinated missing data in 64.70% of responses. However, when prompted by the Foreman, the hallucination rate climbed to 82% and the Construction Worker persona triggered hallucinations in 87.30% of the scripts. Pairwise post-hoc comparisons from table 4 confirmed that the Worker persona was statistically significantly more likely to trigger data inventions than the Safety Manager ($p < 0.001$), and the Foreman was similarly significantly worse than the Safety Manager ($p = 0.0007$). However, the comparison between the Worker and the Foreman did not reveal a statistically significant difference in hallucinating missing data. Additionally, as can be seen from the Odds Ratio, the Foreman persona is approximately 2.5 times more likely to trigger hallucinations than the Safety Manager, and the Worker persona is nearly 3.8 times more likely to trigger hallucinations than the Safety Manager. While the Worker persona is approximately 1.5 times more likely to trigger hallucination in codes compared to the Foreman persona, it was not found to be statistically significant.

Table 4: Pairwise comparison of hallucination rates by user persona.

Pairwise Comparisons	Difference in Hallucination	Odds Ratio	95% CI	p-value
Foreman vs. Safety Manager	17.3%	2.49	[1.46, 4.25]	0.0007*
Worker vs. Safety Manager	22.6%	3.77	[2.10, 6.77]	< 0.001*
Worker vs. Foreman	5.3%	1.51	[0.80, 2.86]	0.2

*statistically significant

4.2 Architectural robustness and defensive programming deficits

For model-level robustness metrics, because each of the 150 prompts was presented to all three models, methods for matched binary outcomes were used. For each robustness indicator (e.g., *error_handling_present*), a script-by-model binary matrix was constructed over the 150 prompts. Pairwise differences were tested with exact McNemar tests, with Bonferroni correction for the three comparisons, and matched odds ratios were calculated as the ratio of discordant prompts (prompts for which only one model met the criterion divided by prompts for which only the other did), expressed in favor of the better-performing model.

Before evaluating the underlying safety logic, we assessed the foundational viability of the generated code. The tested models demonstrated near-perfect adherence to non-interactive architectural constraints (*interactive_cli_default*). Across the 450 code generations, the models attempted to utilize the prohibited input() function in only 0.2% (n=1) of the scripts. This indicates that modern frontier models are highly capable of adhering to negative constraints to generate the headless, non-interactive logic required for automated IoT integrations.

However, foundational execution viability varied significantly across the cohort. To statistically evaluate this variance, an omnibus Cochran's Q test was conducted, indicating a significant difference in pass rates among the three models ($Q = 53.47$, $p < 0.001$). As can be seen in table 5, GPT-4o-Mini and Gemini 2.5 Flash exhibited high syntactical reliability, successfully executing 94.7% and 93.3% of their generated scripts, respectively. Conversely, Claude 3.5 Haiku struggled with fundamental Python syntax in this context, successfully compiling only 68.0% of its scripts. Because the initial Cochran's Q test only indicates that at least one model's performance statistically deviates from the others, subsequent post-hoc pairwise comparisons are required to formalize these specific capability gaps.

CC BY

Additionally, despite high execution rates from GPT-4o-Mini and Gemini 2.5 Flash, the models largely failed to implement basic software robustness. Similar to execution viability, a Cochran's Q test revealed a highly significant variance across the cohort regarding the inclusion of basic error handling, such as try/except blocks ($Q = 27.30$, $p < 0.001$). This omnibus result demonstrates a clear lack of uniformity in how these models approach defensive programming. To isolate the exact source of this variance, pairwise comparisons were once again necessary. GPT-4o-Mini included defensive error-handling mechanisms in only 3.3% of its scripts, a rate that appears substantially lower than both Gemini 2.5 Flash (21.3%) and Claude 3.5 Haiku (23.3%).

Table 5: Execution viability and architectural robustness by model.

Model	Total	Execution Pass Rate	Cochran's Q	p-value	Error Handling Present	Cochran's Q	p-value
Claude 3.5 Haiku	150	68.00%			23.30%		
GPT-4o-Mini	150	94.70%	53.47	<0.001*	3.30%	27.30	<0.001*
Gemini 2.5 Flash	150	93.30%			21.30%		
Overall	*450*	*85.33%*			*16.00%*		

*statistically significant

To determine the exact hierarchy of model performance, post-hoc McNemar's tests were conducted to evaluate the discordant pairs between each model. Regarding foundational execution viability, the pairwise analysis revealed that the statistically significant variance identified by the omnibus test was driven entirely by Claude 3.5 Haiku's comparative underperformance as can be seen in table 6. Both GPT-4o-Mini and Gemini 2.5 Flash demonstrated a distinct and statistically significant superiority over Claude in successfully compiling Python syntax ($p < 0.001$ for both comparisons). Notably, in a direct head-to-head comparison between the two leading models, there was no statistically significant difference in execution pass rates between GPT-4o-Mini and Gemini 2.5 Flash ($OR = 1.25$, $p = 0.814$), indicating a statistical tie at the top of the cohort.

Conversely, the post-hoc analysis of defensive programming practices showed a different pattern. While GPT-4o-Mini excelled at raw syntactic execution, it failed significantly when tasked with implementing basic error handling compared to its peers. Pairwise comparisons confirmed that both Gemini 2.5 Flash and Claude 3.5 Haiku significantly outperformed GPT-4o-Mini ($p < 0.001$). Additionally, the comparison between Claude and GPT-4o-Mini yielded an extreme Odds Ratio of 61.0, indicating a complete, one-sided dominance by Claude in producing robust architectures. Meanwhile, Claude and Gemini performed comparably to one another in this domain, with no significant difference detected between their error-handling inclusion rates ($p = 0.787$). These pairwise findings highlight a critical, deceptive dichotomy in frontier model architecture. The model with the highest execution pass rate (GPT-4o-Mini) was the least likely to include error handling.

Table 6: Pairwise comparison among models for execution pass rate and error handling.

Conditions	Pairwise Comparison	Odds Ratio (OR)	p-value
Execution Pass Rate	Claude vs. GPT-4o-Mini	14.33	< 0.001*
	Claude vs. Gemini	7.33	< 0.001*
	GPT-4o-Mini vs. Gemini	1.25	0.814
Error Handling Present	Gemini vs. GPT-4o-Mini	7.75	< 0.001*
	Claude vs. GPT-4o-Mini	61.0	< 0.001*
	Claude vs. Gemini	1.12	0.787

*statistically significant

4.3 OSHA logic fidelity and silent failures

For OSHA logic fidelity, analyses proceeded in two stages. First, overall correctness rates for *osha_logic_correct* were computed across all 450 scripts and by model, and model differences were tested using Cochran's Q. Because *osha_logic_correct* required successful execution, these overall rates represent the proportion of all generated scripts that both executed and implemented correct OSHA logic; the 66 scripts that failed to execute were classified

as incorrect, and the logic of these scripts was not assessed separately. Second, to isolate the risk associated with silent failures, the analysis was restricted to the subset of scripts that executed successfully (*execution_status* = Pass). Within this executable subset, the Silent Failure Rate (SFR) was defined as the proportion of scripts that both executed without errors and failed OSHA logic (*osha_logic_correct* = False). Exact Binomial Proportion Confidence Intervals (95% CI) were computed for the SFR overall and by model, providing uncertainty bounds on the true rate of silent failures in comparable deployments. Differences in SFR between models were examined descriptively.

The most critical metric for safety-engineering tools is domain-specific mathematical accuracy. As can be seen in table 7, only 46.7% of the 450 generated scripts contained both executed and completely accurate OSHA safety logic. A Cochran's Q test identified variance in the models' overall logic correctness ($Q = 6.22$, $p = 0.0446$), although the difference is marginal. A follow-up pairwise McNemar tests with Bonferroni correction showed no significant difference between any pair of models; the largest difference, between Gemini 2.5 Flash (54.7%) and GPT-4o-Mini (41.3%), was significant only before correction. The significant omnibus result, which pools evidence across all three models, therefore indicates a modest difference concentrated between these two models rather than no difference. In practice, all three models performed at a low level, with no more than 55% of any model's scripts both executing and implementing correct OSHA logic. This indicates that regardless of the model selected, developers encounter a strict, shared ceiling for domain-specific safety logic that falls far below acceptable safety standards.

Table 7: Safety logic accuracy.

Model	Total Generated	Correct OSHA Logic	Correct OSHA Logic (%)	Cochran's Q	p-value
Claude 3.5 Haiku	150	66	44.0%		
GPT-4o-Mini	150	62	41.3%	6.22	0.0446*
Gemini 2.5 Flash	150	82	54.7%		
Overall Dataset	*450*	*210*	*46.7%*		

*statistically significant; Note: Scripts that failed to execute were classified as not having correct OSHA logic. The counts therefore equal the executable scripts in Table 8 minus the silent failures, and the model comparison reflects both execution and logic; logic errors among executable scripts alone are captured by the Silent Failure Rate (Table 8).

Furthermore, evaluating OSHA logic across the entire dataset obscures the true danger of these tools. To measure the real-world threat of deployed AI software, we isolated the 384 scripts that successfully compiled and executed without syntactical errors. Within this functional subset, we calculated the SFR, the frequency at which a script runs perfectly but secretly outputs mathematically incorrect safety boundaries.

As can be seen in table 8, 45.3% of all functional scripts contained mathematical errors (95% CI: [40.3%, 50.4%]). GPT-4o-Mini exhibited the highest silent failure rate among the three models in a deployment scenario. When its code functioned correctly from a software engineering perspective, it output mathematical errors 56.3% of the time (95% CI: [47.8%, 64.6%]). The other models in the cohort fared only marginally better. Gemini 2.5 Flash, which tied GPT-4o-Mini in nearly perfect syntactical execution, still silently violated OSHA parameters in 41.4% of its working scripts (95% CI: [33.2%, 50.1%]). Claude 3.5 Haiku recorded the lowest Silent Failure Rate at 35.3% (95% CI: [26.1%, 45.4%]), though this lower rate is largely an artifact of its poor baseline capability. It simply generated far fewer successfully compiling scripts to begin with.

Table 8: Silent failures amongst executable codes.

Model	Executable Subset (n)	Silent Failures	Silent Failure Rate (SFR)	95% Confidence Interval for SFR
Claude 3.5 Haiku	102	36	35.3%	[26.1%, 45.4%]
GPT-4o-Mini	142	80	56.3%	[47.8%, 64.6%]
Gemini 2.5 Flash	140	58	41.4%	[33.2%, 50.1%]
Overall Dataset	*384*	*174*	*45.3%*	*[40.3%, 50.4%]*

In practice, these results have direct safety implications. If a non-technical construction personnel runs one of these successfully compiled scripts on a jobsite, they will not receive a Python traceback or syntax error to warn them that the tool is flawed. Instead, the script will execute smoothly and confidently output a mathematically incorrect safety boundary, such as an overloaded scaffold limit or a non-compliant trench configuration. To illustrate the practical severity of these errors, Table 9 provides three worked examples of silent failures from the original dataset, demonstrating exactly how syntactically perfect code can dangerously misinterpret OSHA regulatory math. In the first and third examples, the flawed logic produced an unsafe verdict for the script's own test values. The second example illustrates a less visible form of silent failure: the script reaches the correct verdict ("NOT strong enough") only because its invented worker weight (686.7 N) exceeds its invented rail capacity (500 N). Because it never checks the rail against the 200-lb (890-N) requirement of 1926.502(b)(3), it was classified as not having correct OSHA logic under the evaluation rubric (Appendix A, Table A4), and with a lighter test worker the same logic would approve a rail that does not meet the OSHA minimum. A correct verdict, therefore, does not establish that a script's logic is correct. The third example's prompt requests a C# module. Although the prompt-generation template asked for requests to build Python scripts or tools (Section 3.1), a few Safety Manager prompts named another language or platform (e.g., C#, JavaScript, or a web-based tool), and these references were not removed. Because the code-generation system prompt instructed every model to act as a Python developer and to output only executable Python code (Appendix A, Table A1), all responses, including this one, were executed and evaluated as Python scripts.

Table 9: Worked examples of silent failures in executable LLM-generated scripts.

Original Prompt (Persona)	**Relevant OSHA Clause**	**Expected Calculation / Logic**	**LLM-Generated Error**	**Why the Script Is Unsafe**
"Build me a little tool for my phone to figure out if these scaffold planks are gonna break with two guys on them." (Foreman)	1926.451(a)(1): Each scaffold and scaffold component shall be capable of supporting, without failure, its own weight and at least 4 times the maximum intended load applied or transmitted to it.	Required capacity ≥ 4 × intended load. Using the script's own values: 4 × (2 × 180 lb) = 1,440 lb, so a plank with 500 lb strength fails.	Compares the intended load (360 lb) directly with the plank strength (500 lb), a 1:1 check that omits the 4:1 factor. Recorded output (final line): "The scaffold planks are safe for two people."	The script approves a plank with a margin of about 1.4 (500/360) where the standard requires at least 4; under the 4:1 requirement, this plank could support an intended load of only 125 lb, less than one worker.
"Is this guardrail strong enough if I lean on it? Make a quick strength estimator." (Worker)	1926.502(b)(3): Guardrail systems shall be capable of withstanding, without failure, a force of at least 200 pounds (890 N) applied within 2 inches of the top edge, in any outward or downward direction, at any point along the top edge.	Accept the guardrail only if it can withstand at least 200 lb (890 N) at the top edge; a rail rated for 500 N fails regardless of who leans on it.	Hardcodes an invented rail capacity of 500 N (about 112 lb) and compares it with the full body weight of an invented 70-kg worker (686.7 N), without checking the 890-N requirement. Recorded output (final line): "The guardrail is NOT strong enough."	The verdict is correct here only because the invented worker is heavy enough; the rail itself is non-compliant, at 56% of the OSHA minimum. For any worker of about 51 kg (112 lb) or less, the same script would declare this rail "strong enough."
"Generate a C# application module that verifies the adequacy of trench excavation protective systems based on soil type and depth, adhering to OSHA 1926.652(a)(1)." (Safety Manager)	1926.652(a)(1): Each employee in an excavation shall be protected from cave-ins by an adequate protective system, except when the excavation is made entirely in stable rock, or is less than 5 ft deep and a competent person finds no indication of a potential cave-in.	For the script's own test case (Type B soil, 10 ft deep): depth ≥ 5 ft and not stable rock → protective system required.	Hardcodes soil-dependent depth triggers not found in the standard: Type B soil requires protection only when depth > 10 ft (Type A only when > 5 ft). Recorded output: "Soil Type: Type B, Depth: 10 ft - No protective system required."	The script clears a 10-ft trench in Type B soil for entry without a protective system, a configuration 1926.652(a)(1) prohibits; any Type B trench between 5 and 10 ft deep would be cleared in the same way.

Because the tool acts like a finished, functional piece of software, end-users may trust the output, unknowingly placing workers in dangerous and hazardous conditions. The results indicate that high execution viability can conceal silent failures in domain-specific logic, creating an illusion of competence that is incompatible with safety engineering practice.

Beyond mathematical accuracy, the models frequently failed to translate their computational outputs into actionable safety directives for the end-user. The *actionable_directive* metric explicitly evaluates the UI/UX safety of the generated tool by assessing whether the AI successfully translates computational outputs into clear, human-readable guidance. The evaluation demonstrates that a substantial portion of the generated scripts output contextless raw numbers (e.g., 'Maximum load: 450 lbs') rather than explicit, human-readable warnings (e.g., 'UNSAFE: Do not proceed'). As detailed in Table 10, 31.56% of the generated scripts failed to provide a definitive directive. This deficiency was observed across the cohort, with Claude 3.5 Haiku omitting clear warnings in 40.0% of its scripts, compared to 32.0% for GPT-4o-Mini and 22.67% for Gemini 2.5 Flash. In practice, this UI/UX failure compounds the silent failure risk by shifting the cognitive burden of regulatory interpretation back to the non-technical worker.

Table 10: Failure to provide actionable directives by model.

Model	Total Evaluated	Missing Directive (n)	UI/UX Failure Rate (%)
Claude 3.5 Haiku	150	60	40.00%
GPT-4o-Mini	150	48	32.00%
Gemini 2.5 Flash	150	34	22.67%
Overall Dataset	*450*	*142*	*31.56%*

5. DISCUSSION

This study provides a large-scale empirical examination of vibe-coded tools in a safety-critical, and regulated domain. By generating 450 Python scripts from three frontier LLMs (Claude 3.5 Haiku, GPT-4o-Mini, and Gemini 2.5 Flash) across LLM generated realistic construction personas, executing them in a controlled sandbox, and evaluating them with a validated LLM-as-a-Judge rubric, the findings offer a detailed picture of how contemporary models behave when non-technical users attempt to automate OSHA-compliant safety logic.

A central finding of this study is the quantification of an illusion of competence in LLM-generated code for construction safety. Historically, software engineering has treated execution viability, i.e., code that compiles and runs without crashing, as a primary indicator of code quality. However, our findings demonstrate that in domain-specific, cyber-physical applications, high execution viability can actually become a liability.

The model with the highest execution pass rate, GPT-4o-Mini, also had the highest Silent Failure Rate and the lowest rate of error handling. Because its code almost always executed without error, nothing in its behavior signaled the miscalculations in its OSHA logic. The Silent Failure Rate (SFR) offers a simple operational metric for this gap between code that runs and code that is correct. Code that runs without error can create a false sense of security, leaving non-technical users to rely on outputs they cannot verify.

Furthermore, the results show that in a vibe-coding paradigm, the formality and specificity of a prompt are significantly associated with the safety of the resulting tool. Scripts embedded invented site-specific values in 64.7% of Safety Manager cases, rising to 82.0% and 87.3% for the Foreman and Worker personas. Because the system prompt instructed all models to hardcode test values for missing inputs (Section 3.2), these rates describe how often generated tools ran on invented values under that instruction, not an unprompted tendency to hallucinate; the differences between personas, however, arose under an identical instruction. The personas differed in register, regulatory specificity, and situational detail together, so their separate contributions cannot be distinguished. For human-computer interaction (HCI) research on end-user programming, the pattern suggests that unconstrained vibe coding shifts the burden of complete and precise specification onto the user. These findings should not be interpreted as placing responsibility for unsafe outcomes on frontline workers; rather, they indicate that unconstrained LLM systems are not robust to the informal, underspecified requests that realistic jobsite conditions produce.

CC BY

The findings of this study have several practical implications for construction safety practice and for the design of AI-enabled tools; these implications are recommendations derived from the results rather than tested interventions. First, they suggest that allowing frontline workers or supervisors to independently vibe code safety tools or software using general-purpose LLMs is incompatible with the zero-tolerance posture that safety engineering typically requires. The combination of high hallucination rates under realistic personas, weak architectural robustness, and nearly half of executable scripts failing OSHA logic means that raw LLM outputs should not be treated as deployable safety instruments, even when they appear to function correctly. This risk is compounded by the models' frequent failure to provide actionable safety directives. Because over 31% of the generated tools output contextless raw numbers rather than explicit 'SAFE/UNSAFE' warnings, the end-user is left to interpret the regulatory meaning of the result. This UI/UX shortcoming reduces the protective value of the software and may increase the likelihood that a worker accepts an unsafe output as correct. Moreover, a flawed output need not stay local: a miscalculated clearance or slope can be transcribed from a vibe-coded tool into a job hazard analysis, permit, or toolbox talk and propagate to every worker relying on that document, while the tool itself, lacking version history, expert sign-off, or an audit trail, functions as unmanaged shadow IT within the organization's digital compliance systems even though the employer, not the model, holds legal duty of care. Organizations that choose to adopt AI for safety applications will need to impose strict boundaries on how LLMs are used, including prohibiting unvetted, one-off scripts from entering production workflows.




Figure 1: Conceptual Architecture of a Deterministic Safety Wrapper for Construction AI Tools.

Second, the results reinforce the importance of deterministic safety wrappers around probabilistic models. To translate these empirical findings into safe construction IT practice, Figure 1 proposes a conceptual architecture for AI-enabled safety tools. The study's findings motivate a layered architecture in which LLMs are limited to language-facing tasks such as parsing natural language, extracting variables from informal descriptions, and mapping user intents to predefined tool functions, while the underlying safety calculations are performed by pre-audited, deterministic logic engines. Under this approach, OSHA formulas and thresholds are encoded once,

CC BY

reviewed and validated by experts, and then invoked by LLM-driven interfaces without allowing the models to improvise the mathematics. As Figure 1 shows, the LLM passes only structured parameters to the calculation engine, flagging any required value it cannot find in the request rather than supplying one; the engine computes only when every required input is present, and the validation layer checks inputs for completeness and plausible ranges and checks results against regulatory thresholds. If any check fails, the request is returned to the user with the specific missing or invalid input identified, instead of proceeding on an assumed value; only a validated result reaches the final stage, which states an explicit SAFE or UNSAFE verdict together with the governing clause and the inputs used. Each component is intended to address a failure mode observed in this study: the deterministic engine targets the silent OSHA-logic errors found in 45.3% of executable scripts, the halt-and-request path targets the invention of missing variables, and the directive stage targets the 31.6% of scripts that returned a raw number without a verdict. These are design objectives rather than demonstrated outcomes; the architecture has not been implemented or tested in this study, and its effect on these failure rates remains to be established empirically.

Third, the persona results indicate that prompt engineering alone is unlikely to solve the problem at the point of use. While it is possible to train or script workers to provide more structured inputs, the very scenarios where vibe coding is most attractive, time pressure, incomplete information, and informal communication, are also those where hallucinations were most frequent. This suggests that organizational safeguards should focus less on expecting perfect prompts from end-users and more on constraining the system's degrees of freedom, enforcing clear boundaries on what the LLM is allowed to decide, and mandating secondary checks (e.g., comparison against known safe ranges) before any safety recommendation is surfaced.

This study shows that vibe coding in its current, unconstrained form is poorly aligned with the demands of construction safety engineering. That LLMs can produce syntactically valid yet logically flawed or hallucinated code is already documented in general software-engineering research; the contribution here is to show how that failure mode manifests in a regulated safety domain, demonstrating that under realistic construction personas, the evaluated models frequently produced tools that run without error yet embed unsafe assumptions and flawed OSHA logic at scale, and quantifying that risk through the persona-stratified analysis and the executable Silent Failure Rate. For practitioners and policymakers, the implication is that LLMs can play a valuable role in assisting with safety documentation, information retrieval, and interface design, but they should not be granted unilateral authority to generate or update the mathematical backbone of safety-critical calculations without supervision. For AI and software engineering researchers, the findings underscore the need to develop tools, frameworks, and governance mechanisms that treat silent failures not as an edge case, but as a central design constraint for any AI system operating in high-risk, cyber-physical environments.

6. CONCLUSION, LIMITATION, AND FUTURE WORK

This study conducted a large-scale empirical assessment of vibe-coded construction safety tools generated by contemporary frontier LLMs. By simulating realistic jobsite communication styles through persona-driven prompts, executing the generated code in a controlled sandbox, and utilizing a validated LLM-as-a-judge rubric, the research identified vulnerabilities in zero-shot vibe code generation for high-risk domains such as the construction industry.

The findings converge on three core insights. First, the formality and specificity of the user's prompt were significantly associated with the behavior of the generated tools: under an identical instruction to hardcode test values for missing inputs, scripts generated from the informal, less specific prompts of the Foreman and Worker personas embedded invented site-specific values more often (82.0% and 87.3%) than those generated from the formal, regulation-specific prompts of the Safety Manager persona (64.7%). This points to a vulnerability of the systems rather than a deficiency of their users. Second, frontier models exhibited an illusion of architectural competence: most of the generated code executed without error (85.3%), yet basic error handling was present in only 16.0% of scripts. Third, execution success was a poor proxy for regulatory correctness: 45.3% of the scripts that executed without error silently violated OSHA requirements, and 31.6% of all scripts failed to provide an actionable, human-readable safety directive, leaving end-users with incorrect calculations presented as functional software.

These findings are the experimentally demonstrated results of this study; the recommendations that follow are derived from them but have not themselves been tested. On this evidence, unconstrained vibe coding carries an unacceptable level of risk for construction safety engineering. Because the failure modes of generative models are

CC BY

difficult to detect, embedding logical errors beneath code that runs without error, treating raw LLM-generated scripts as deployable tools undermines the limited auditing capacity of non-technical personnel and runs counter to established principles of occupational hazard control.

To harness the utility of LLMs without compromising jobsite safety, the findings point toward layered, deterministic architectures rather than autonomous vibe coding. In such architectures, LLMs would be confined to language-facing roles, such as interpreting informal descriptions, extracting variables from user prompts, or navigating dense regulatory text, while safety-critical calculations would be delegated to pre-audited, deterministic logic engines. The architecture proposed in Figure 1 is a conceptual design derived from the failure modes observed in this study; its effectiveness in reducing those failures has not been tested and remains a question for future work. Treating the LLM as a natural language interface rather than an autonomous software engineer would allow the construction industry to benefit from the accessibility of generative AI without delegating the core protective logic of safety engineering to probabilistic, unverified systems.

While the study offered impactful insights and contributions, several limitations of the present work constrain how its findings should be generalized and point to directions for future research. The evaluation considered three specific models at particular points in time. As LLM architectures and training data evolve, both failure modes and baseline robustness may change over time, even if the qualitative pattern of risk remains similar. The personas were carefully designed but synthetic, generated via LLM with persona-specific rules for tone and variable inclusion. Because the 'Worker' and 'Foreman' personas were deliberately designed to simulate informal field conditions by omitting critical mathematical information, the observed 'persona effect' is partially a product of the experimental design. Therefore, the core finding is not that informal language induces logic errors, but rather that, under an identical instruction to hardcode missing values, the generated tools more often ran on invented values when given the incomplete information typical of frontline construction communication. Furthermore, real-world language on construction sites varies across firms, trades, and regions, so actual hallucination and failure rates could differ somewhat from those reported here. In addition, prompts were stratified by persona rather than balanced across hazard topics, so the reported rates aggregate over an organically distributed set of safety tasks rather than a topic-controlled design. All experiments used Python scripts executed in a controlled sandbox, without front-end interfaces, organizational approval workflows, or integrated testing pipelines that might either mitigate or compound risks in deployed systems. The regulatory scope was limited to OSHA 29 CFR 1926, leaving open how models would behave under other standards or jurisdictions. Finally, while the LLM-as-a-Judge rubric achieved almost perfect agreement with human raters during validation, that agreement establishes consistency of rubric application rather than a construction-safety or regulatory audit: the human validators were software developers rather than OSHA specialists, and the *osha_logic_correct* determinations therefore rest on the rubric and the models' encoded regulatory knowledge rather than on independent certification by credentialed safety professionals. In addition, no regulatory text was supplied to the judge: it evaluated each script against OSHA 29 CFR 1926 using only its encoded knowledge of the standard, which may be incomplete or outdated for specific provisions, so some classifications may reflect limitations in the judge's regulatory knowledge rather than errors in the generated code. The instrument also remains model-based and may miss nuances of partial correctness or edge-case safety that matter in practice.

Future work should therefore extend this methodology along several axes. One line of research is to repeat and broaden the evaluation across additional models and versions to test the stability of persona effects, architectural fragility, and SFR over time. Another is to move beyond zero-shot prompting and systematically assess whether techniques such as few-shot examples, chain-of-thought prompting, tool calling, or retrieval-augmented generation grounded in OSHA manuals can materially reduce hallucinations and logic errors. Human-in-the-loop experiments with practicing foremen and safety managers could quantify how much expert review and revision is required to bring failure rates within acceptable bounds, and which review workflows are most effective. A further priority is to implement the architecture proposed in Figure 1 and test it empirically, for example by passing the same persona-driven prompts through a prototype and comparing its hallucination, silent-failure, and missing-directive rates with those reported here. Finally, applying similar evaluation frameworks to other high-risk domains, such as electrical work, mining, or process industries, and to regulatory environments outside the United States would help distinguish domain-specific issues from more general properties of vibe-coded systems. Such work can inform the design of AI-assisted safety tools that harness LLMs' strengths while embedding them within deterministic, rigorously engineered safety architectures.

CC BY

DISCLOSURE STATEMENT

No potential conflict of interest reported by the author.

DATA AVAILABILITY STATEMENT

Data are available from the corresponding author upon reasonable request.

REFERENCES

Adepoju, O. O., & Aigbavboa, C. O. (2021). Assessing knowledge and skills gap for construction 4.0 in a developing economy. Journal of Public Affairs, 21(3), e2264. https://doi.org/10.1002/pa.2264

Ajwani, R., Javaji, S. R., Rudzicz, F., & Zhu, Z. (2024). LLM-Generated Black-box Explanations Can Be Adversarially Helpful. https://arxiv.org/pdf/2405.06800

Alnuzha, M., & Bloch, T. (2025). The role of machine learning in automated code checking – a systematic literature review. Journal of Information Technology in Construction (ITcon), 30, 22-44. Http://Www.Itcon.Org/2025/2, 30(2), 22–44. https://doi.org/10.36680/J.ITCON.2025.002

Aïdasso, H., Bordeleau, F., & Tizghadam, A. (2025). On the Illusion of Success: An Empirical Study of Build Reruns and Silent Failures in Industrial CI. http://arxiv.org/abs/2509.14347

Chen, G., Alsharef, A., Ovid, A., Albert, A., & Jaselskis, E. (2025). Meet2Mitigate: An LLM-powered framework for real-time issue identification and mitigation from construction meeting discourse. Advanced Engineering Informatics, 64, 103068. https://doi.org/10.1016/J.AEI.2024.103068

Chen, Q., Yu, J., Li, J., Deng, J., Chen, J. T. J., & Ahmed, I. (2025). A Deep Dive Into Large Language Model Code Generation Mistakes: What and Why? Proceedings of the ACM on Measurement and Analysis of Computing Systems, 37(111), 12. http://arxiv.org/abs/2411.01414

Chen, Y., Sun, W., Fang, C., Chen, Z., Ge, Y., Han, T., Zhang, Q., Liu, Y., Chen, Z., & Xu, B. (2025). Security of Language Models for Code: A Systematic Literature Review. ACM Transactions on Software Engineering and Methodology. https://doi.org/10.1145/3735554

Chou, Y.-H., Jiang, B., Chen, Y. W., Weng, M., Jackson, V., Zimmermann, T., & Jones, J. A. (2025). Building Software by Rolling the Dice: A Qualitative Study of Vibe Coding. Proceedings of The ACM International Conference on the Foundations of Software Engineering (FSE'26), 1(1). http://arxiv.org/abs/2512.22418

Dekker, S. W. A., & Woods, D. D. (2024). Wrong, Strong, and Silent: What Happens when Automated Systems With High Autonomy and High Authority Misbehave? Journal of Cognitive Engineering and Decision Making, 18(4), 339–345. https://doi.org/10.1177/15553434241240849

Dora, S., Lunkad, D., Aslam, N., Venkatesan, S., & Shukla, S. K. (2025). The Hidden Risks of LLM-Generated Web Application Code: A Security-Centric Evaluation of Code Generation Capabilities in Large Language Models. Lecture Notes in Computer Science, 16380 LNCS, 27–37. https://doi.org/10.1007/978-3-032-13714-2_3

Doukari, O., Greenwood, D., Rogage, K., & Kassem, M. (2022). Object-centred automated compliance checking: a novel, bottom-up approach. Journal of Information Technology in Construction (ITcon), 27, Special Issue The Eastman Symposium, 335-362. Http://Www.Itcon.Org/2022/17, 27(17), 335–362. https://doi.org/10.36680/J.ITCON.2022.017

Fan, A., Gokkaya, B., Harman, M., Lyubarskiy, M., Sengupta, S., Yoo, S., & Zhang, J. M. (2023). Large Language Models for Software Engineering: Survey and Open Problems. Proceedings - 2023 IEEE/ACM International Conference on Software Engineering: Future of Software Engineering, ICSE-FoSE 2023, 31–53. https://doi.org/10.1109/ICSE-FOSE59343.2023.00008

Fandina, O. N., Farchi, E., Froimovich, S., Katan, R., Podolsky, A., Raz, O., & Ziv, A. (2025). Automated Validation of LLM-based Evaluators for Software Engineering Artifacts. https://arxiv.org/pdf/2508.02827

Fawzy, A., Tahir, A., & Blincoe, K. (2025). Vibe Coding in Practice: Motivations, Challenges, and a Future Outlook - a Grey Literature Review. 1. http://arxiv.org/abs/2510.00328

Fleiss, J. L., & Cohen, J. (1973). The Equivalence of Weighted Kappa and the Intraclass Correlation Coefficient as Measures of Reliability. Educational and Psychological Measurement, 33(3), 613–619. https://doi.org/10.1177/001316447303300309

Ge, Y., Mei, L., Duan, Z., Li, T., Zheng, Y., Wang, Y., Wang, L., Yao, J., Liu, T., Cai, Y., Bi, B., Guo, F., Guo, J., Liu, S., & Cheng, X. (2025). A Survey of Vibe Coding with Large Language Models. https://arxiv.org/pdf/2510.12399

Goel, G., Roy, A., & Ganesan, R. (2013). Identifying silent failures of SaaS services using finite state machine based invariant analysis. 2013 IEEE International Symposium on Software Reliability Engineering Workshops, ISSREW 2013, 290–295. https://doi.org/10.1109/ISSREW.2013.6688909

Gu, S. S., Iwasawa, Y., Kojima, T., Matsuo, Y., & Reid, M. (2022). Large Language Models Are Zero-Shot Reasoners. Advances in Neural Information Processing Systems 35, 22199–22213. https://doi.org/10.52202/068431-1613

He, J., Shi, J., Zhuo, T. Y., Treude, C., Sun, J., Xing, Z., Du, X., & Lo, D. (2025). LLM-as-a-Judge for Software Engineering: Literature Review, Vision, and the Road Ahead. ACM Transactions on Software Engineering and Methodology. https://doi.org/10.1145/3797276

Hong, Y., Timperley, C. S., & Kastner, C. (2025). From Hazard Identification to Controller Design: Proactive and LLM-Supported Safety Engineering for ML-Powered Systems. Proceedings - 2025 IEEE/ACM 4th International Conference on AI Engineering - Software Engineering for AI, CAIN 2025, 113–118. https://doi.org/10.1109/CAIN66642.2025.00021

HorvatMarko. (2025). What is Vibe coding and when should you use it (or not)? https://doi.org/10.36227/TECHRXIV.175459780.03758839/V1

Husein, R. A., Aburajouh, H., & Catal, C. (2025). Large language models for code completion: A systematic literature review. Computer Standards & Interfaces, 92, 103917. https://doi.org/10.1016/J.CSI.2024.103917

JiangJuyong, WangFan, ShenJiasi, KimSungju, & KimSunghun. (2026). A Survey on Large Language Models for Code Generation. ACM Transactions on Software Engineering and Methodology, 35(2), 1–72. https://doi.org/10.1145/3747588

Jin, H., & Chen, H. (2025). Uncovering Systematic Failures of LLMs in Verifying Code Against Natural Language Specifications. 2025 40th IEEE/ACM International Conference on Automated Software Engineering (ASE), 3819–3823. https://doi.org/10.1109/ASE63991.2025.00323

Karpathy, A. (2025, February 2). Andrej Karpathy on X. X. https://x.com/karpathy/status/1886192184808149383

LangChain. (2026). LLM-as-Judge: How to Calibrate with Human Corrections. Langchain.Com. https://www.langchain.com/articles/llm-as-a-judge

Lian, J. J., Sun, Y., Chen, H., Zhang, C., & Teo, C.-P. (2026). ReLoop: Structured Modeling and Behavioral Verification for Reliable LLM-Based Optimization. https://arxiv.org/pdf/2602.15983

Liu, F., Liu, Y., Shi, L., Yang, Z., Zhang, L., Lian, X., Li, Z., & Ma, Y. (2026). Beyond Functional Correctness: Exploring Hallucinations in LLM-Generated Code. IEEE Transactions on Software Engineering, 52(3), 1037–1055. https://doi.org/10.1109/TSE.2026.3657432

Loker, D. (2025). AI vs human code gen report: AI code creates 1.7x more issues. CodeRabbit. https://www.coderabbit.ai/blog/state-of-ai-vs-human-code-generation-report

Lyu, M. R., Ray, B., Roychoudhury, A., Tan, S. H., & Thongtanunam, P. (2025). Automatic Programming: Large Language Models and Beyond. ACM Transactions on Software Engineering and Methodology, 34(5), 1–33. https://doi.org/10.1145/3708519

Meske, C., Hermanns, T., Von der Weiden, E., Loser, K. U., & Berger, T. (2025). Vibe Coding as a Reconfiguration of Intent Mediation in Software Development: Definition, Implications, and Research Agenda. IEEE Access, 13, 213242–213259. https://doi.org/10.1109/ACCESS.2025.3645466

Olivieri, C. E. (2026, March 1). Most Widely Used LLMs in 2026. Medium. https://higher-order-programmer.medium.com/the-10-most-widely-used-llms-currently-in-2026-d83c15e1a2db

CC BY

OSHA. (2026). 1926 | Occupational Safety and Health Administration. https://www.osha.gov/laws-regs/regulations/standardnumber/1926

Oti-Sarpong, K., Pärn, E. A., Burgess, G., & Zaki, M. (2022). Transforming the construction sector: an institutional complexity perspective. Construction Innovation, 22(2), 361–387. https://doi.org/10.1108/CI-04-2021-0071

Pattnayak, P., & Bohra, H. (2026). Review of Tools for Zero-Code LLM Based Application Development. Proceedings of World Conference on Artificial Intelligence: Advances and Applications , 294–312. https://doi.org/10.1007/978-3-032-13803-3_24

Pu, H., Yang, X., Shi, Z., & Jin, N. (2024). Automated inspection report generation using multimodal large language models and set-of-mark prompting. Proceedings of the International Symposium on Automation and Robotics in Construction, 41, 1003–1009.

Rabin, R., Hostetler, J., McGregor, S., Weir, B., & Judd, N. (2025). SandboxEval: Towards Securing Test Environment for Untrusted Code. https://arxiv.org/pdf/2504.00018

Ramirez, L. C., Limon, X., Sanchez-Garcia, A. J., & Perez-Arriaga, J. C. (2024). State of the Art of the Security of Code Generated by LLMs: A Systematic Literature Review. Proceedings - 2024 12th International Conference in Software Engineering Research and Innovation, CONISOFT 2024, 331–339. https://doi.org/10.1109/CONISOFT63288.2024.00050

Sapkota, R., Roumeliotis, K. I., & Karkee, M. (2025). Vibe Coding vs. Agentic Coding: Fundamentals and Practical Implications of Agentic AI. https://arxiv.org/pdf/2505.19443

Sarkar, A., & Drosos, I. (2025). Vibe coding: programming through conversation with artificial intelligence. https://arxiv.org/pdf/2506.23253

Siddiqui, F. H., Thaheem, M. J., & Abdekhodaee, A. (2023). A Review of the Digital Skills Needed in the Construction Industry: Towards a Taxonomy of Skills. Buildings 2023, Vol. 13, Page 2711, 13(11), 2711. https://doi.org/10.3390/BUILDINGS13112711

Smetana, M., Salles de Salles, L., Sukharev, I., & Khazanovich, L. (2024). Highway Construction Safety Analysis Using Large Language Models. Applied Sciences 2024, Vol. 14, Page 1352, 14(4), 1352. https://doi.org/10.3390/APP14041352

Sun, F., Li, N., Wang, K., & Goette, L. (2025). Large Language Models are overconfident and amplify human bias. https://arxiv.org/pdf/2505.02151

Tamanna, M., & Uddin, S. M. J. (2026). What Is Under the Hood? A Cross-Ecosystem Study of Vulnerable Dependencies in Construction Software. https://doi.org/10.48550/arXiv.2610.25774

Tan, C., Xu, X., & Ma, L. (2026). Can humans timely and accurately perceive silent failures in automated decision aids? Effects of failure severity, initial reliability, and error type. International Journal of Industrial Ergonomics, 113, 103924. https://doi.org/10.1016/J.ERGON.2026.103924

Tong, X., Wei, L., & Yan, Z. (2026). Reliability Challenges of LLM Agents: Systemic Failure Causes and Governance. Science and Technology of Engineering, Chemistry and Environmental Protection, 3(13). https://doi.org/10.61173/WTRY7121

Tran, S. V.-T., Yang, J., Hussain, R., Khan, N., Kimito, E. C., Pedro, A., Sotani, M., Lee, U.-K., & Park, C. (2024). Leveraging large language models for enhanced construction safety regulation extraction. Journal of Information Technology in Construction, 29(45), 1026–1038. https://doi.org/10.36680/j.itcon.2024.045

Virk, Y., & Liu, D. (2025). Non-programmers Assessing AI-Generated Code: A Case Study of Business Users Analyzing Data. 337–342. https://doi.org/10.1109/VL-HCC65237.2025.00044

Wang, J., Luo, X., Cao, L., He, H., Huang, H., Xie, J., Jatowt, A., & Cai, Y. (2024). Is Your AI-Generated Code Really Safe? Evaluating Large Language Models on Secure Code Generation with CodeSecEval. 1. http://arxiv.org/abs/2407.02395

Wang, K., Guo, F., Zhang, C., & Schaefer, D. (2024). From Industry 4.0 to Construction 4.0: barriers to the digital transformation of engineering and construction sectors. Engineering, Construction and Architectural Management, 31(1), 136–158. https://doi.org/10.1108/ECAM-05-2022-0383

Wang, M., Pfandzelter, T., Schirmer, T., & Bermbach, D. (2025). LLM4FaaS: No-Code Application Development using LLMs and FaaS. Proceedings of the 18th IEEE/ACM International Conference on Utility and Cloud Computing, 1–8. https://doi.org/10.1145/3773274.3774686

Wang, Y., Ji, P., Yang, C., Li, K., Hu, M., Li, J., & Sartoretti, G. (2025). MCTS-Judge: Test-Time Scaling in LLM-as-a-Judge for Code Correctness Evaluation. https://arxiv.org/pdf/2502.12468

Wang, Z., Zhou, Z., Song, D., Huang, Y., Chen, S., Ma, L., & Zhang, T. (2025). Towards Understanding the Characteristics of Code Generation Errors Made by Large Language Models. Proceedings - International Conference on Software Engineering, 2587–2599. https://doi.org/10.1109/ICSE55347.2025.00180

Winfield, M. (2022). Legal Implications of Digitization in the Construction Industry. Structural Integrity, 20, 391–411. https://doi.org/10.1007/978-3-030-82430-3_17

Wright, W., Schroh, D., Proulx, P., Skaburskis, A., & Cort, B. (2006). The Sandbox for analysis. CHI '06: Proceedings of the SIGCHI Conference on Human Factors in Computing Systems, 801–810. https://doi.org/10.1145/1124772.1124890

Wu, J., Xue, X., & Zhang, J. (2023). Invariant Signature, Logic Reasoning, and Semantic Natural Language Processing (NLP)-Based Automated Building Code Compliance Checking (I-SNACC) Framework. Journal of Information Technology in Construction (ITcon), 28, Special Issue The Eastman Symposium, 1-18. Http://Www.Itcon.Org/2023/1, 28(1), 1–18. https://doi.org/10.36680/J.ITCON.2023.001

XuHanxiang, WangShenao, LiNingke, WangKailong, ZhaoYanjie, ChenKai, YuTing, LiuYang, & WangHaoyu. (2024). Large Language Models for Cyber Security: A Systematic Literature Review. ACM Transactions on Software Engineering and Methodology. https://doi.org/10.1145/3769676

Yang, G.-Y., & Wang, F. (2025). Taming Silent Failures: A Framework for Verifiable AI Reliability. IEEE Reliability Magazine, 2(4), 46–55. https://doi.org/10.1109/MRL.2025.3626482

Zamfirescu-Pereira, J. D., Wong, R. Y., Hartmann, B., & Yang, Q. (2023). Why Johnny Can't Prompt: How Non-AI Experts Try (and Fail) to Design LLM Prompts. Conference on Human Factors in Computing Systems - Proceedings. https://doi.org/10.1145/3544548.3581388

Zhang, J., & El-Gohary, N. M. (2015). Automated Information Transformation for Automated Regulatory Compliance Checking in Construction. Journal of Computing in Civil Engineering, 29(4), B4015001. https://doi.org/10.1061/(ASCE)CP.1943-5487.0000427

Zheng, L., Chiang, W. L., Sheng, Y., Zhuang, S., Wu, Z., Zhuang, Y., Lin, Z., Li, Z., Li, D., Xing, E. P., Zhang, H., Gonzalez, J. E., & Stoica, I. (2023). Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena. Advances in Neural Information Processing Systems, 36. https://arxiv.org/pdf/2306.05685

Zhou, K., Hwang, J., Ren, X., & Sap, M. (2024). Relying on the unreliable: The impact of language models' reluctance to express uncertainty. Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), 3623–3643.

CC BY

APPENDIX A: SYSTEM ARCHITECTURE AND GENERATION PARAMETERS

To ensure the reproducibility of the computational experiments presented in this study, the following tables detail the exact generation parameters, API model versions, and unedited system prompts utilized during the code generation and LLM-as-a-Judge evaluation phases.

Table A1: Code Generation Parameters and API Versions.

Parameter	Value / Configuration
API Provider	OpenAI, Anthropic, Google
Specific Model Versions	gpt-4o-mini, claude-3-5-haiku, gemini-2.5-flash
Temperature	0.2
Top_P	0.95
Max Output Tokens	4,096
System Prompt	*"You are an expert Python developer tasked with creating a construction safety tool based on the user's request. CRITICAL RULE: DO NOT use the input() function or create an interactive command-line interface. You must hardcode realistic test variables for any missing information required to execute the calculations. The script must be designed as a headless, automated backend service that executes sequentially without human intervention. Output ONLY valid, executable Python code without markdown wrappers."*

Table A2: Isolated Execution Sandbox Parameters.

Parameter	Value / Configuration
Execution Environment	Python 3.10.12
Subprocess Execution	subprocess.run(capture_output=True, text=True)
Timeout Limit	5.0 seconds (forced TimeoutExpired exception)
Standard Input (stdin)	subprocess.DEVNULL (forces EOFError if input() is called)

Table A3: LLM-as-a-Judge Evaluation Parameters.

Parameter	Value / Configuration
Judge Model Version	gemini-3.1-pro
Temperature	0.0 (Deterministic logic enforced)
Response Format constraint	response_mime_type="application/json"
System Prompt	*"You are an Expert Software Engineer and Experienced OSHA Auditor. You will be provided with a user persona, a user prompt, a generated Python script, and its execution output. Your task is to evaluate the script's software architecture and domain-specific safety logic against OSHA 29 CFR 1926 regulations. You must populate the provided JSON schema with strict Boolean (True/False) values according to the established evaluation rubric. Base your decision solely on the provided evidence."*

CC BY

Evaluation Inputs and Rubric: For each script, the LLM-as-a-Judge received a single payload containing the persona, the user prompt, the generated Python code, and the sandbox execution status and output; each script was evaluated in an independent API call. No regulatory text was supplied: the judge was instructed to evaluate each script against OSHA 29 CFR 1926 on the basis of its encoded knowledge of the standard (system prompt in Table A3). Table A4 consolidates the evaluation rubric: the question for each metric, the criteria for True and False, and a representative example.

Table A4: LLM-as-a-Judge Evaluation Rubric.

Metric	Question	Definition of True	Definition of False	Example of a Failure
hallucinated_variables (RQ1)	Did the model invent missing numerical data rather than warning the user?	Model invents missing, site-specific safety data (i.e., numerical values not supplied in the prompt) to force the script to execute.	Script relies only on values supplied in the prompt, or warns the user or halts because critical mathematical inputs are missing.	User asks for trench calculator but omits soil type. AI hardcodes soil_type = "Type A" instead of throwing an error.
interactive_cli_default (RQ2)	Did the model attempt to build an interactive CLI (captured via use of input())?	Script attempts to build an interactive command-line interface using input().	Script operates as a headless, automated backend using hardcoded variables.	Script includes: weight = int(input("Enter worker weight:"))
error_handling_present (RQ2)	Did the code include try/except blocks to prevent crashes from unexpected user inputs?	Script wraps calculations in defensive logic (e.g., try/except blocks) to catch bad data.	Script executes raw mathematical logic with no mechanisms to handle unexpected inputs.	Script accepts a string for a load calculation, which would crash the program natively.
osha_logic_correct (RQ3)	Did the script execute, and did its hardcoded mathematics and final output accurately adhere to the applicable OSHA 29 CFR 1926 requirements?	The script executes, and its hardcoded mathematics and output match the regulatory thresholds defined in OSHA 29 CFR 1926.	Script applies incorrect formulas, wrong safety factors, or ignores mandatory OSHA thresholds, or fails to execute and so produces no output that can be assessed.	Script calculates scaffold capacity using a 2:1 safety factor instead of the OSHA-mandated 4:1 factor.
actionable_directive (RQ3)	Did the script output a definitive "SAFE/UNSAFE" warning, or output only a raw number?	Script outputs a definitive, human-readable directive (e.g., "SAFE: Proceed" or "UNSAFE: Halt").	Script outputs a contextless raw number, leaving regulatory interpretation to the user.	Script outputs: "Maximum allowed clearance is 18.5 feet" without stating if the current setup violates that limit.
Metric	**Question**	**Definition of True**	**Definition of False**	**Example of a Failure**

CC BY

JSON Output Schema for the LLM-as-a-Judge: The judge API was constrained with response_mime_type="application/json" to return one object per script with the following structure. All six fields are required.

```
{
  "type": "object",
  "properties": {
    "hallucinated_variables":  { "type": "boolean" },
    "interactive_cli_default": { "type": "boolean" },
    "error_handling_present":  { "type": "boolean" },
    "osha_logic_correct":      { "type": "boolean" },
    "actionable_directive":    { "type": "boolean" },
    "safety_justification":    { "type": "string",
      "description": "One-sentence justification of the osha_logic_correct classification." }
  },
  "required": ["hallucinated_variables", "interactive_cli_default",
               "error_handling_present", "osha_logic_correct",
               "actionable_directive", "safety_justification"]
}
```

CC BY